



JME18

MODEL	DESCRIPTION	
JME18	<p>Boom deflexion; Canopy; Kubota Euro5 engine; Expanding tracks; Hydraulic quick hitch; Bucket width 400mm; 260mm narrow bucket; 1000mm cleaning bucket Heater&fan; Radio, Hammer pipes; Open front window, Rubber track;</p>	

Picture



Attachments:

800mm cleaning bucket			Rake		
800mm tilting bucket			Auger		
Grapple			Ripper		
300mm bucket			Hammer		
1000mm tilting bucket			600mm bucket		

Specifications:

Engine

Model	Kubota D1105-EF09 engine, Euro5
Power	14kw/2200rpm

Main Performance

Swing Speed	r/min	10-12
Traveling Speed	km/H	2.8
Grade ability	%	70(35°)
Traveling Tracking Force	kN	15
Bucket Digging Force	kN	11.5

Arm Digging Force	kN	9.3
-------------------	----	-----

Hydraulic System

Hydraulic system working pressure	Mpa	16
Hydraulic Pump	Gear Pump	AHWY
Hydraulic pump flow	L/min	22×2+8.8
Swing Motor		Eaton
Traveling Motor		Eaton
Fuel Tank Capacity	L	26
Hydraulic Tank Capacity	L	27

Overall Dimensions

Overall Length	mm	3800
Overall Width	mm	1050
Overall Height	mm	2280
Ground clearance	mm	485
Track length	mm	1630
Track width	mm	230
Undercarriage width	mm	1050
Undercarriage ground clearance	mm	235

Operation parameters

Operation Weight	KG	1800
Bucket Capacity	m ³	0.06
Max. Digging Radius	mm	3860
Max. Digging Depth	mm	2050
Max. Digging Height	mm	3370
Max. Dumping Height	mm	2390
Max. Dozer Cutting	mm	270
Max. Dozer Lifting	mm	235
Boom Deflexion (Left/Right)	°	75/45

J Mac Excavators Ltd, Whitehouse Farm, Malthouse Lane, Earlswood, Solihull, Warwickshire, United Kingdom, B94 5DX

T. +44 (0)1564 336633 E. sales@jmacuk.com www.jmacuk.com
Company registered in England & Wales, Number 11291171